

MY SHELTERS

Quality is our Topmost Priority

An ISO 9001: 2015 CO.

THE EXCLUSIVE HUB OF CUSTOMIZED ROOFINGS & WALL PANELS

A GLANCE THROUGH PRODUCTS




PUF ROOF & WALL PANEL


Product Features


- » High load bearing capacity at low weight.
- Excellent and durable thermal insulation.
- Sound Proof & Fire Resistance (PI)
- » Pre engineered product for precise dimensions and accuracy.
- Quick on-site installation. High Structural durability and longevity.

Product Specification

1	PUF Thickness (MM)	Standard Width (M)	Standard Length (M)	Standard PUF Density	Standard Colours
	20 upto 150	1.06 & 1.16	As per requirements	40 KG/M3	Off-White, Brick Red, Royal Blue, Sky Blue, Green, Grev









POLYCARBONATE SHEET

Product Features

- » High Impact Strength.
- » Lightweight.
- » Heat Resistance.
- Easy to Fabricate & Machine
- » Non Breakable

Category

- » Multiwall
- >> Honeycomb
- » Plain Solid
- >> Diamond
- Embossed
- >> Raindrop
- Maze, River, Box
- Profile AC, GC, TATA, JSW

PUF Thickness (MM)	Standard Width (M)	Standard Length (M)	Standard PUF Density	Standard Colours
1 upto 20	4, 5, 7	39, 100	1.20-1.22 g/cm3	Clear, Greenish blue, Bronze, Blue, Pencil Grey









UPVC SHEET

Product Features

- » Anti-Corrosion
- Sound absorption and heat insulation
- » Long life and Durability

Product Specification

- » Low Maintenance
- Environment Friendly
- Cost-Effective
- Waterproof roofing sheets

Standard Thickness (MM)	Standard Width (FT)	Standard Length (FT)	Standard Density	Standard Colours
2.3, 2.5	3.5	4, 8, 10, 12, 16.5	1.47 gm/cc	Brick Red, Grey, Chocolate Brown









STONE COATED METAL SHEET

Product Features

- Stone-coated steel is more durable
- Metal roofing with the aesthetic appeal of traditional roofing materials
- » No maintenance
- Environment Friendly
- » Attractive Appearance

Standard Thickness (MM)	Standard Density	Standard Colours	
1.5	8050 kg/m3	Forest Green, Black-Red, Garnet, Charcoal, Coffee Brown, Ocean Blue	









METAL ROOFING SHEET

Product Features

- » Cost efficient.
- Surface-treated steels are all resistant to pressure, corrosion and wear and tear.
- Fire Retardant.

Product Specification

Standard Thickness (MM)	Standard Width (M)	Standard Length (M)	Sta
0.30 upto 0.60	1.06	As per requirements	

Category

- » Tata Profile
- » Kerala Tile Profile
- » Bond tile Profile
- » Long Span Corrugate Tile Profile
- » Linear Profile

Standard Thickness (MM)	Standard Width (M)	Standard Length (M)	Standard Density	Standard Colours	
0.30 upto 0.60	1.06	As per requirements	8050 kg/m3	Off- White, Royal Blue, Brick Red, Grey	











XLPE & BUBBLE INSULATION SHEET

Product Features

- Outstanding weather stability.
- Easy fabrication.
- High resistance to wear and tear.
- VOC-free at 80°C (Heat resistant at 110°C).
- Excellent moisture and flame resistance.
- Resistance to crush and heat deformation.

	Standard Thickness (MM)	Standard Width (M)	Standard Length (M)	Standard Density	Standard Materials
XLPE	6 upto 20	1.22	20 upto 40	30Kg/M²	Aluminium
BUBBLES	4 upto 25	1.25	20 upto 40	8150 Nos/Sq mt.	Aluminium









DECKING SHEET

Product Features

- » Reduces the construction cost significantly.
- Reduces the slab thickness and deadweight of the building and reduces the quantity of steel required during construction.
- » Deck sheets are strong and durable.
- » Resilience towards moisture built-up and weather damage.
- Decking sheets expedite the pace of construction


Product Specification

Standard Thickness (MM)	Standard Width (MM)	Standard Length (M)	Standard Depth (MM)
0.80 upto 2	931	As per requirements	50
0.80 upto 2	915	As per requirements	75









TURBO VENTILATOR & POLYCARBONATE BASE

Product Features

- Permanently lubricated and Sealed ZZ bearings.
- » No maintenance Rust free.
- » Rain proof rugged spider design.

- » Highly durable
- >> Unbreakable, fire retardant, UV resistant
- Easy to handle and install

	Ventilato	r Diameter	Top Co	ver	Bottom Pla	te for Blade	В	lade
Turbo Ventilator Fan	Outer Diameter	22, 24 Inch	Thickness	0.5 mm	Thickness	0.5 mm	Length	430 mm
Polycarboate Base	Diameter	22, 24 Inch	Thickness	2 mm	Length	1.7 M	Profile	AC, TATA, GI, GC, JSW
Aluminium Base	Diameter	22, 24 Inch	Thickness	0.5 mm	Length	1.22 M	Profile	Plain









INTERIOR & EXTERIOR WALL PANELS

Product Features

- » Customizable solution for modern designs of wall
- Easy installation
- » Low Maintenance

- » 100 % water and fire resistant
- Excellent Durability
- » Classic wood grain looks

Product Specification

Standard Thickness (MM)	Standard Width (FT)	Standard Length (FT)	Standard Colours	Materials
2 upto 10	0.5,1,4	8,10,12	Multi Colour	PVC, UPVC, WPC, HPL









CEILING PANELS

Product Features

- Modern decorative designs for ceilings
- » Hide imperfections of the ceiling and improve the thermo-acoustic comfort of the rooms.
- Easy installation

- » Low Maintenance
- 3 100 % water and fire resistant
- Excellent Durability
- Classic wood grain looks

Standard Thickness (MM)	Standard Width (FT)	Standard Length (FT)	Standard Colours	Materials
6 to 10	1	8,10,12	Multi Colour	PVC, WPC

















ROOFING SCREWS

Product Features

- Designed to withstand extensive corrosion testing
- » protocols and environments
 Wide material compatibility
- High Strength-to-Weight Ratio

Product Specification

Thickness (MM)	Length (MM)	COATING
10, 12	20 to 150	Xylan, Grey, Ruspert, Zinc

MS & GI PIPE

Product Features

- » Highly tensile
- Corrosion resistance, high temperature resistance, and superior impact resistance
- Cost-effective and Recyclable





ACCESSORIES



UPVC RAIN GUTTER



MS CUTTING WHEEL



GP SEALANT SILICONE



UPVC DOOR & WINDOW



MARBLE CUTTING WHEEL



Z&CPURLIN



METAL LOUVER



WOOD CUTTING WHEEL



ANCHOR FASTENERS



POLYCARBONATE LOUVER



WELDING ELECTRODE



THOOVANAM



- myshelterstry@gmail.com
- www.myshelters.co.in
- GSTIN 33HISPS0940G1ZX
- Durairaj Valarmathi Enclave, Near ZEE SCHOOL, MM Nagar, Tiruchirappalli, Tamil Nadu 620102.
- No 57, Mela Kalnayakan Street, Woraiyur, Tiruchirappalli, Tamil Nadu 620003.

